



Safety Data Sheet

SECTION 1. IDENTIFICATION

GHS Product Identifier:	Bagged EZ Mix
Other Means of Identification:	Concrete Mix, Concrete Mix with Air, Sand Mix, Mortar Mix
Recommended Use:	Pre- mix bag applications. Construction.
Restrictions On Use:	N/A
Canadian Supplier Identifier+:	Fisher Wavy Inc. P.O Box 2000 Copper Cliff, ON P0M 1N0
Emergency Phone Number:	(705) 674-4291

SECTION 2: HAZARD IDENTIFICATION

GHS Classification and Category:	Skin Corrosion/Irritation- skin irritation (Category 1,1A, 1B, and C). Serious Eye Damage/Eye Irritation-eye irritation- (Category 2 and 2A). Specific Target Organ Toxicity- repeated exposure (Category 1 and 2). Respiratory or Skin Sensitization-respiratory sensitizer (Category 1, 1A, and 1B).
---	---

GHS Label Elements
Hazard Pictograms:
Signal Word:



Hazard Statement:	Danger Causes severe skin burns and eye damage. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.
Precautionary Statement(s)	
General:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Prevention:	Do not breathe dust. Wash any exposed body parts. Contaminated clothing must not leave the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Response:	If exposed or concerned: Get medical advice/attention if rash or irritation occurs. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse continuously with water for several minutes. If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center/doctor.
Storage:	Restrict and control access to stockpile areas. Engulfment hazard: To prevent burial or suffocation, do not enter a confined space without an effective procedure for assuring safety.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazards Not Otherwise Classified (HNOC):	Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions or illnesses.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name: Bagged EZ Mix

Chemical Abstract Service (CAS) registry number and unique identifiers:

Component	Percentage (%)	CAS Number
Cement	15-40%	65997-15-1
Ferric Oxide	11-15	148808-60-7
Sodium Carbonate	15-40	n/a
Calcium Oxide	6-8	1305-78-8
Chromium Oxide	0.3-0.4	n/a
Crystalline Silica	0-0.2 (<1%)	14808-60-7
Alluminum Oxide	7-10	1344-28-1
Pozzolan (Amorphous Silica)	1-5	n/a
Silica, non-crystalline (combined silica, fumed silica)	23-32	n/a

Component Information on Non-Hazardous Components:

N/A

SECTION 4. FIRST AID MEASURES

First Aid

Eye contact:

If exposed or concerned: get medical attention. Do not allow individual to rub eyes. Immediately flush eyes gently under running water, do not attempt to remove material from eyes. Obtain medical attention for eye contact with wet cement.

Skin contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Call physician if irritation persists.
Ingestion:	Do not induce vomiting. If conscious, drink milk. Seek medical attention if any problems arise.
Inhalation:	Remove to fresh air. Obtain medical attention if breathing difficulties persist.
<i>Most important symptoms and effects (acute or delayed)</i>	
Inhalation:	May irritate nose and throat if dust inhaled. Prolonged or repeated inhalation of respirable dust may lead to respiratory tract or lung damage.
Skin contact:	Cement may contain trace amounts of hexavalent chromium and is linked with allergic sensitization reactions in some individuals. These reactions may lead to contact dermatitis and skin ulceration. Exposure to dust from dry ingredients or hardened cement can cause skin irritation, dermatitis and/or redness to the exposed skin. Exposure to dust from dry ingredients or hardened cement can cause irritation and tearing of the eyes. Exposure to wet cement may result in irritation or burns.
Eye contact:	Immediate or delayed irritation or inflammation. Can be as severe as blindness. Get proper medical attention.
Ingestion:	Is not a common route of occupational exposure. If swallowed and irritation or burns occurs, obtain medical attention.
Immediate medical attention and special treatment, if necessary:	If you feel unwell, seek medical advice (show the label where possible).

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Not combustible. Use extinguishing agent appropriate for surrounding flammable materials.
--------------------------------------	---

Unsuitable extinguishing media:	N/A
Specific hazards arising from the chemical:	Not combustible. Nonflammable. Spalling of hardened cement may occur under conditions of intense heat.
Hazardous thermal decomposition products:	Material is not combustible.
Special protective equipment and precautions for fire-fighters:	Material is nonflammable. Use appropriate procedures for surrounding flammable materials. Use PPE appropriate for surrounding materials. No specific precautions.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

For response personnel: Keep unprotected personnel out of the area. Do not dry sweep dusty material. All local and Federal laws governing waste disposal must be followed.

Environmental precautions: Clean spilled material immediately. Contain spills and wash water to prevent run-off into public waterways. Remove wet cement from roadways immediately. Do not dry sweep spilled dust material.

Methods and material for containment and clean up

Containment: Proper PPE.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Use proper PPE. Remove contaminated clothing as soon as possible. Dust may be generated during handling or mixing dry powder or from cutting,

breaking or crushing hardened material. Use wet cutting methods where possible. Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work.

**Conditions for safe storage
 (including incompatible materials)**

Technical measures: Comply with applicable regulations.
Storage conditions: Keep/store away from incompatible materials.
Incompatible materials: Strong acids, strong bases, strong oxidizers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters
 Component exposure
 limits:**


INGREDIENT NAME:	EXPOSURE LIMITS:
Particulates and not otherwise classified (CAS SEQ250)	ACGIH TLV (U.S, 3/2012) TWA: 3 mg/m3. Form: Respirable particles TWA: 10 mg/m3. Form: Inhalable particles OSHA PEL (U.S, 6/2010) PEL: 5 mg/m3. Form Respirable fraction PEL: 15 mg/m3. Form: Total dust TWA: 5 mg/m3. Form: Respirable fraction TWA: 15 mg/m3. Form: Total dust
Cement	ACGIH TLV (U.S, 3/2012) TWA: 0.025 mg/m3. Form: Respirable dust OSHA PEL (U.S, 6/2012) PEL: 10 mg/m3. Form: Respirable dust PEL: 30 mg/m3. Form: Total dust
Crystalline Silica (Quarz) (CAS 14808-60-7)	ACGIH TLV (U.S, 3/2012) TWA: 3mg/m3. Form: Respirable dust TWA: 10mg/m3. Form: Total dust OSHA PEL (U.S, 6/2012) PEL: 5mg/m3. Form: Respirable dust PEL: 15mg/m3. Form: Total dust

Appropriate engineering controls:

Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment (PPE):

Protective goggles or safety glasses with side shields. Gloves. Protective clothing. Dust formation: dust mask.



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (Physical state, colour etc.):	Solid (powder), grey off-white or white
Odour:	N/A
Odour threshold:	N/A
pH:	N/A
Freezing point:	N/A
Initial boiling point/boiling range:	N/A
Flash point:	N/A
Evaporation rate:	N/A
Flammability (solid; gas):	N/A
Lower flammable/explosive limit:	N/A
Upper flammable/explosive limit:	N/A
Vapour pressure:	N/A
Vapour density:	N/A
Relative density:	N/A
Solubility:	Negligible
Partition coefficient-n-octanol/water:	N/A
Auto-ignition temperature:	N/A
Specific Gravity:	2.69-2.9
Viscosity:	N/A

SECTION 10. STABILITY AND REACTIVITY

Reactivity:	Hazardous reactions will not occur under normal conditions. Stable. Reacts with water creating heat and calcium hydroxide.
Chemical stability:	Stable under recommended handling and storage conditions.
Possibility of hazardous reactions:	None. Hazardous polymerization will not occur.
Conditions to avoid:	Moisture or wetting will cause exothermic heating as product cures.
Incompatible materials:	Keep dry until used. Avoid contact with incompatible compounds.
Hazardous decomposition products:	Reacts with water to form calcium hydroxide which can irritate/damage skin. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on Toxicological Effects-Product

Acute toxicity:	Not classified															
Corrosion/irritation:	Skin: May cause skin burns or skin ulcers. Eye: May cause eye irritation or serious eye damage. Respiratory: Increased risk of lung cancer from chronic exposure to crystalline silica. Also, silicosis, autoimmune diseases, and kidney disorders.															
Sensitization:	May cause sensitization due to trace amounts of hexavalent chromium.															
Carcinogenicity:	See chart below.															
Specific target organ toxicity (repeated exposure):	<table border="1"> <thead> <tr> <th>Product:</th> <th>OSHA</th> <th>IARC</th> <th>ACGIH</th> <th>NTP</th> </tr> </thead> <tbody> <tr> <td>Portland Cement</td> <td>-</td> <td>-</td> <td>A4</td> <td>-</td> </tr> <tr> <td>Crystalline Silica (Quartz)</td> <td>-</td> <td>1</td> <td>A2</td> <td>Know to be human carcinogen</td> </tr> </tbody> </table>	Product:	OSHA	IARC	ACGIH	NTP	Portland Cement	-	-	A4	-	Crystalline Silica (Quartz)	-	1	A2	Know to be human carcinogen
Product:	OSHA	IARC	ACGIH	NTP												
Portland Cement	-	-	A4	-												
Crystalline Silica (Quartz)	-	1	A2	Know to be human carcinogen												
Reproductive toxicity:	Not classified.															
Specific target organ																

Fisher Wavy Inc.
 Safety Data Sheet: Bagged EZ Mix
 According to GHS 2015 Rules and Regulations

toxicity (single exposure):	Name:	Category	Route of Exposure	Target Organs
	Crystalline Silica (quartz)	-	Inhalation	Not reported to have effects
Specific target organ toxicity (repeated exposure): Chronic symptoms:	Name	Category	Route of Exposure	Target Organs
	Crystalline Silica (Quartz)	-	Inhalation	May cause damage to organs (lung) through prolonged or repeated exposure.
Potential Chronic health effects: General:	Prolonged inhalation of respirable crystalline silica may be harmful. May cause damage to organs (lung) through prolonged or repeated exposure. Also, autoimmune disorders, silicosis and kidney failures.			
Aspiration hazards:	Not classified.			

SECTION 12. ECOLOGICAL INFORMATION
 (information is optional)

Ecotoxicity:	No additional information available
Persistence and degradability:	N/A
Bioaccumulative potential:	N/A
Mobility in soil:	N/A
Other adverse effects:	Avoid release to the environment.

SECTION 13. DISPOSAL CONSIDERATIONS
 (information is optional)

<i>Waste Disposal</i>	
Recommendations:	Dispose of waste material in accordance with all


local/regional/national/provincial/territorial/and international regulations.
Ecology- Waste Materials: Avoid release to the environment.

**SECTION 14. TRANSPORT INFORMATION
(information is optional)**

UN number: N/A
UN proper shipping name: N/A
Transport hazard class(es): N/A
Packing group: N/A
Environmental hazards: N/A
Transport in bulk, if applicable: Follow MTO regulations
Special precautions: Follow all rules and regulations.

**SECTION 15. REGULATORY INFORMATION
(information is optional)**

Canadian Regulations
Bagged EZ Mix
WHMIS
classification: Class D Division 2 Subdivision A- Very toxic material causing other toxic effects



Quartz (14808-60-7) Listed on the Canadian DSL (Domestic Substance List)
Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration: 1%

WHMIS
Classification: Class D Division 2 Subdivision A- Very toxic material causing other toxic effects
Class D Division 2 Subdivision B- Toxic material causing other toxic effects

SECTION 16. OTHER INFORMATION

Revision date:	February 28, 2017
Other Information:	This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

“The information provided herein is believed by seller to be accurate at the time of preparation, or prepared from sources believed to be reliable. Health and Safety precautions in this data sheet may not be adequate for all individuals or situations. Users have the responsibility to comply with all laws and procedures applicable to the safe handling and use of the product, to determine the suitability of the product for its intended use, and to understand possible hazards associated with mixing this product with other materials. SELLER MAKES NOWARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT, THE MERCHANTABILITY, OR FITNESS THEROF FOR ANY PURPOSE, CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY SELLER.”